

NEW Illuma Product Comparison Goes Live!

Illuma are pleased to announce that their new product comparison feature is now live!

Specifying lighting is an important process and choosing the perfect lighting solution is essential.

At Illuma we thoroughly believe that good lighting stems from creating atmosphere and ambience alongside the practical application of light. Lighting should not just be seen as a functional solution but instead as an intrinsic part of the experience.

Illuma have developed a brand-new product comparison feature on the company's website that allows customers to select products and then compare their specifications and features.

Illuma Product Comparison

				
Range	Prospect LED	Prospect LED	Prospect LED	Prospect LED
Product Type	Spotlights	Spotlights	Spotlights	Spotlights
Product Description	Prospect 22W 1800lm 3000K 15° Black G3 Leading edge	Prospect 22W 1800lm 4000K 15° Black G3 Leading edge	Prospect 22W 1800lm 3000K 15° White G3 Leading edge	Prospect 22W 1800lm 4000K 15° White G3 Leading edge
Product Code	T361815 BL/G1DL/930	T361815 BL/G1DL/940	T361815 WH/G1DL/930	T361815 WH/G1DL/940
Body Colour	Black	Black	White	White
Mounting	Track Mounted	Track Mounted	Track Mounted	Track Mounted
Track Adaptor	G1DL - 1-Circuit Multi Track Adaptor	G1DL - 1-Circuit Multi Track Adaptor	G1DL - 1-Circuit Multi Track Adaptor	G1DL - 1-Circuit Multi Track Adaptor
Pendant Stem Length(mm)	-	-	-	-
Vertical Mount	-	-	-	-
Environment	Interior	Interior	Interior	Interior
Size(mm)	160 x 105 x 85	160 x 105 x 85	160 x 105 x 85	160 x 105 x 85
Cut Out(mm)	-	-	-	-
Recessed Depth(mm)	-	-	-	-
Vertical Tilt(°)	90°	90°	90°	90°
Horizontal Rotation(°)	355°	355°	355°	355°
Light Source	LED	LED	LED	LED
Lamp Type	Luminous	Luminous	Luminous	Luminous
Lamp Included	In Built	In Built	In Built	In Built
Lamp Base	-	-	-	-
Lamp Life(Hours)	50000 hours	50000 hours	50000 hours	50000 hours
Lumen Output(lm)	1800lm	1800lm	1800lm	1800lm
Colour Temperature(K)	3000K Warm White	4000K Neutral White	3000K Warm White	4000K Neutral White
CRI(Ra)	92	92	92	92
Beam Angle(°)	15°	15°	15°	15°
Voltage	230VAC	230VAC	230VAC	230VAC
Total System Power(W)	24.3W	24.3W	24.3W	24.3W
Lamp Current(A)	0.108	0.108	0.108	0.108
Power Factor	-	-	-	-
Luminaire Efficacy(lm/W)	74lm/W	74lm/W	74lm/W	74lm/W
Class	Class 1	Class 1	Class 1	Class 1
Gear	Built In	Built In	Built In	Built In
EAN Code	-	-	-	-
Dimmability	Leading/Trailing Edge Dimmable	Leading/Trailing Edge Dimmable	Leading/Trailing Edge Dimmable	Leading/Trailing Edge Dimmable
Emergency	-	-	-	-
IP Rating	IP20	IP20	IP20	IP20
Weight(kg)	0.75kg	0.75kg	0.75kg	0.75kg
Housing Material	Aluminium	Aluminium	Aluminium	Aluminium
Material Finish	Powder Coated	Powder Coated	Powder Coated	Powder Coated
Guarantee	5 Year Guarantee	5 Year Guarantee	5 Year Guarantee	5 Year Guarantee
Downloads	  	  	  	  