

# Ground lights

## GL100

Up to 2W, 14lm mini domed marker ground light



Guarantee / Warranty: 7 year extended warranty available




Stainless steel



Antique Brass



1 way



2 ways 1 direction



2 ways 2 directions



3 ways



4 ways

### PHOTOMETRICS @ 25°C

Product Code	Finish	Window Style	Colour	Beam Angle	350mA			700mA		
					Wattage	lm	lm/W	Wattage	lm	lm/W
GL100DX1X40	Stainless steel	1 way	4000K	75°	1W	3	3	2W	4	2
GL100DX1X30	Stainless steel	1 way	3000K	75°	1W	2	2	2W	4	2
GL100DX1X27	Stainless steel	1 way	2700K	75°	1W	2	2	2W	3	2
GL100DX2140	Stainless steel	2 ways 1 direction	4000K	75°	1W	6	6	2W	7	4
GL100DX2130	Stainless steel	2 ways 1 direction	3000K	75°	1W	4	4	2W	8	4
GL100DX2127	Stainless steel	2 ways 1 direction	2700K	75°	1W	4	4	2W	6	3
GL100DX2240	Stainless steel	2 ways 2 directions	4000K	75°	1W	6	6	2W	7	4
GL100DX2230	Stainless steel	2 ways 2 directions	3000K	75°	1W	4	4	2W	8	4
GL100DX2227	Stainless steel	2 ways 2 directions	2700K	75°	1W	4	4	2W	6	3
GL100DX3X40	Stainless steel	3 ways	4000K	75°	1W	9	9	2W	11	5
GL100DX3X30	Stainless steel	3 ways	3000K	75°	1W	6	6	2W	12	6
GL100DX3X27	Stainless steel	3 ways	2700K	75°	1W	6	6	2W	9	5
GL100DX4X40	Stainless steel	4 ways	4000K	75°	1W	12	12	2W	14	7
GL100DX4X30	Stainless steel	4 ways	3000K	75°	1W	8	8	2W	14	7
GL100DX4X27	Stainless steel	4 ways	2700K	75°	1W	8	8	2W	12	6
GL100AX1X30	Antique brass	1 way	3000K	75°	1W	2	2	2W	4	2
GL100AX1X27	Antique brass	1 way	2700K	75°	1W	2	2	2W	3	2
GL100AX2130	Antique brass	2 ways 1 direction	3000K	75°	1W	4	4	2W	8	4
GL100AX2127	Antique brass	2 ways 1 direction	2700K	75°	1W	4	4	2W	6	3
GL100AX2230	Antique brass	2 ways 2 directions	3000K	75°	1W	4	4	2W	8	4
GL100AX2227	Antique brass	2 ways 2 directions	2700K	75°	1W	4	4	2W	6	3
GL100AX3X30	Antique brass	3 ways	3000K	75°	1W	6	6	2W	12	6
GL100AX3X27	Antique brass	3 ways	2700K	75°	1W	6	6	2W	9	5
GL100AX4X30	Antique brass	4 ways	3000K	75°	1W	8	8	2W	14	7
GL100AX4X27	Antique brass	4 ways	2700K	75°	1W	8	8	2W	12	6


### INSTALLATION INFORMATION

Input	350mA / 700mA
Dimmable	Requires driver
Cut-out size	Ø33mm
Construction material	Stainless steel (316) Antique brass: Brass
Weight	Stainless steel: 221g (1 window) 218g (2 windows) 215g (3 windows) 212g (4 windows) Antique brass: 236g (1 window) 231g (2 windows) 228g (3 windows) 223g (4 windows)
Class	Class III
Max. ambient temperature	35°C

### BENEFITS

- Can be powered by either a 350mA or 700mA driver, depending on desired light output
- Marine-grade Stainless Steel 316
- Walk over - perfect for foot traffic areas such as paths and steps
- Long-lifetime of 70,000hrs
- Low power consumption of 2W max.
- up to 18kN (approx. 7 ton vehicle)
- Suitable for coastal areas

### SIZE DIAGRAM



### ACCESSORIES

JB2 / JB4 / JB6	IP68 waterproof connectors	TUBE332	Installation tube
-----------------	----------------------------	---------	-------------------