

60/61 - LOW VOLTAGE SCREW WIRING 90° ANGLED SURFACE MOUNTING INLETS

IP67

GW61453



LOW VOLTAGE SCREW WIRING 90° ANGLED SURFACE MOUNTING INLETS FOR HIGH CURRENTS



Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Pack Carton
RATED CURRENT (A): 63						
GW 61 445	2P+E	100 - 130 V	■	50/60 Hz	4	2/4
GW 61 446	3P+E	100 - 130 V	■	50/60 Hz	4	2/4
GW 61 447	3P+N+E	100 - 130 V	■	50/60 Hz	4	2/4
GW 61 448	2P+E	200 - 250 V	■	50/60 Hz	6	2/4
GW 61 449	3P+E	200 - 250 V	■	50/60 Hz	9	2/4
GW 61 450	3P+N+E	200 - 250 V	■	50/60 Hz	9	2/4
GW 61 451	2P+E	380 - 415 V	■	50/60 Hz	9	2/4
GW 61 452	3P+E	380 - 415 V	■	50/60 Hz	6	2/4
GW 61 453	3P+N+E	346 - 415 V	■	50/60 Hz	6	2/4
GW 61 454	3P+E	480 - 500 V	■	50/60 Hz	7	2/4
GW 61 455	3P+N+E	480 - 500 V	■	50/60 Hz	7	2/4
RATED CURRENT (A): 125						
GW 60 456	3P+E	100 - 130 V	■	50/60 Hz	4	1/2
GW 60 457	3P+N+E	100 - 130 V	■	50/60 Hz	4	1/2
GW 60 458	3P+E	200 - 250 V	■	50/60 Hz	9	1/2
GW 60 459	3P+N+E	200 - 250 V	■	50/60 Hz	9	1/2
GW 60 460	3P+E	380 - 415 V	■	50/60 Hz	6	1/2
GW 60 461	3P+N+E	346 - 415 V	■	50/60 Hz	6	1/2
GW 60 462	3P+E	480 - 500 V	■	50/60 Hz	7	1/2
GW 60 463	3P+N+E	480 - 500 V	■	50/60 Hz	7	1/2

CHARACTERISTICS: PG21 cable gland for 16-32A versions; PG36 cable gland for 63A versions; PG48 cable gland for 125A versions. 63A and 125A versions equipped with a pilot contact.

ACCESSORIES FOR PLUGS

IP67

GW60264



WATERTIGHT COVERS FOR PLUGS

Code	For inlets	Pack Carton
RATED CURRENT (A): 16		
GW 60 263	2P+E	10/120
GW 60 264	3P+E	10/120
GW 60 265	3P+N+E	10/80
RATED CURRENT (A): 32		
GW 60 266	2P+E and 3P+E	8/64
GW 60 267	3P+N+E	8/64