# essentials™

Product Code: CL052

## **Technical Specification**

Luckinslive 389086486

Description: 13A Double Pole Switched Fused Connection Unit With Neon & Optional Flex





#### **General Information**

Dimensions (mm) 80 (W) x 80 (H) x 42 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

Style Metal Clad Colour Grey

Materials Insert, Switch, Fuse Drawer & Housing: Urea

Terminals: Brass Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Neon Lens: Polycarbonate

Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass

Operating Voltage (AC) 250 Frequency (Hz) 50

Resistive Load Rating (A)

Fuse Fitted Type Plug Top Cartridge Fuse

Termination Type Screw

Terminal Size (mm) Ø5 Terminal Torque Value (Nm) 2

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Switched Yes Double Pole Switch Twin Earth Terminals Yes

Neon Indicator Yes Indicator Colour Red

Flex Outlet Available Yes

Flex Outlet Location Front of Plate Flex Outlet Dimension (mm) Ø10

Supplied Back Box Depth (mm) Back Box Knockouts - Total (mm) 5 x Ø20

Back Box Knockouts - Sides (mm) 1 x Ø20 Back Box Knockouts - Top (mm) 2 x Ø20 Back Box Knockouts - Rear (mm) None Back Box Knockouts - Bottom (mm) 1 x Ø20

Back Box Earth Terminal Supplied

Ingress Protection IP20 Operational Temperature (°C) -5 to +40 Warranty (Years)

**Standards** BS 1363-4, BS 1362

### **Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal

Specification is subject to change without notice. Errors & Omissions excluded.









