

Product Code: CMA100

Technical Specification

Luckinslive 389087126



Description: 115V/230V Dual Voltage Shaver Socket Outlet





Rear Housing: Urea

General Information

Plate Dimensions (mm) 86 (W) x 146 (H) x 9.5 (D)

Plate Fixing Centres - Vertical (mm) 120.6

> Rounded Profile Style Colour Polar White Materials Front Plate: Urea

> > Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Anti Microbial Certified Operating Voltage (AC) Frequency (Hz) 50/60 220-240

Load Rating @115V (Va) 20 Load Rating @230V (Va)

Thermal Protection Device PTC Resettable Fuse

> Termination Type Screw

Terminal Size (mm) Ø3.5 Terminal Torque Value (Nm) 0.5

Terminal Capacity - Solid (mm²) 2 x 1.5 or 1 x 2.5

Socket Features Safety Interlock Shutter

Twin Farth Terminals Yes

Product Marking Shavers Only, 230V~, 115V~

Minimum Back Box Depth (mm) Ingress Protection

Operational Temperature (°C) -5 to +40

> Warranty (Years) Warranty - Electronics (Years) 2

Standards BS EN IEC 61558-1, BS EN 61558-2-5

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

This outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet.

CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2-5:2010 making it safe for use in bathrooms.

PTC resettable fuses increase resistance as temperature increases due to increased flow. PTC resettable fuses are designed to limit unsafe currents while allowing constant safe current levels, resistance will "reset" automatically when the fault is removed and temperature returns to

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom

T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com









