

AREELEDWL/PIR



Features

Durable outdoor bi-directional wall light

Only suitable for semi commercial applications

Polycarbonate construction ideal for coastal applications

CCT selectable between 3000K, 4000K and 6000K

Unique lockable installation base plate with push fit loop-in loopout terminals for ease of installation

Discrete PIR option available

LED lifespan L80 54,000 hours

Non-dimmable

General Information

Lamp Type	LED
IP Rating	IP65
Class Protection	2
Internal / External	Internal / External
Surface / Recessed / Suspended	Surface
Warranty (Years)	3
CE Mark	Yes
Diameter (mm)	85
Height (mm)	170

Technical Information

Wattage	10W
Lumens Delivered	815lm (Warm White), 885lm (Cool White), 860lm (Daylight)
Lm/W	82lm (Warm White), 89lm (Cool White), 86lm (Daylight)
Beam Angle	90
CRI	Ra 80
CCT	3000/4000/6000K
Input	230V
Hertz	50Hz
Operating Temp	-20°C to 40°C

Technical Data - ETIM - Ceiling-/wall luminaire (EC002892)

Suitable for wall mounting	Yes
Suitable for suspended mounting	No
Suitable for ceiling mounting	No
Suitable for built-in mounting	No
Suitable for surface mounting	Yes
With light source	Yes
Material housing	Plastic
Nominal voltage	230-230 V
Control gear included	Yes
No dim function	Yes
Beam angle	Extreme wide beam >80°
Degree of protection (IP)	IP65
Protection class	II
Suitable for emergency lighting	No
With movement sensor	Yes
With light sensor	No
Max. system power	10 W
Colour of light	White
Colour temperature	3000-6000 K
Colour rendering index CRI	80-89
Length	170 mm
Outer diameter	85 mm

Datasheet generated from <https://onetimepim.com> last updated Monday, September 6, 2021 1:34:21 PM