

AKESLED/3M



Features

Ultra slim suspended LED emergency exit sign

Self-test emergency as standard

LiFePO4 Lithium battery provides improved energy consumption, product reliability and lifetime

Supplied with arrow down legend as standard. Up, left and right legends can be supplied upon request

Viewing distance 24 metres

General Information

Lamp Type	LED
Colour / Finish	White
Self Test	Yes
IP Rating	IP20
Class Protection	1
Internal / External	Internal
Surface / Recessed / Suspended	Suspended
Warranty (Years)	5
CE Mark	Yes
Length (mm)	276
Width (mm)	37
Accessories	AKESLED/ALAR, AKESLED/L/AD, AKESLED/L/AU, ASBP/22

Technical Information

Wattage	2W
Lumens Delivered	14lm (Emergency)
CCT	6500K
Input	230V
Hertz	50Hz
Operating Temp	0C° to 40C°



Technical Data - ETIM - Emergency luminaire (EC001957)

Mounting method	Pendant
Function	Escape route signage
Monitoring equipment	Automatic self test
With light source	Yes
Colour housing	White
Nominal voltage	230-230 V
Degree of protection (IP)	IP20
Protection class	I
Max. system power	2 W
Colour temperature	6500-6500 K
Recognition distance	24 m
Width	37 mm
Length	276 mm

Datasheet generated from <https://onetimepim.com> last updated Monday, September 6, 2021 1:25:52 PM

