



ATURWOLED/70/WW



Features

- Powerful compact LED inground uplight
- Exceeds performance of 50W Halogen
- Die-cast aluminium construction with 316L stainless steel top frame
- Static load test to 2000kg
- Supplied c/w installation housing for additional protection and ease of installation
- Pre-wired with 1 metre of rubber insulated cable
- LED lifespan L70 50,000 hours
- Non-dimmable

General Information

Lamp Type	LED
Colour / Finish	Stainless Steel
IP Rating	IP67
IK Rating	IK10
Class Protection	1
Internal / External	External
Surface / Recessed / Suspended	Recessed
Warranty (Years)	5
CE Mark	Yes
Diameter (mm)	68
Depth (mm)	140
Accessories	ATURWOLED/70/2, ATURWOLED/70/4

Technical Information

Wattage	3W
Lumens Delivered	124lm
Lm/W	41lm
Beam Angle	26
CRI	Ra 80
CCT	3000K
Input	230V
Hertz	50/60Hz
Operating Temp	-20 to 25°C

Technical Data - ETIM - In-ground luminaire (EC000758)

With light source	Yes
Suitable for number of lamps	1
Colour housing	Stainless steel
Nominal voltage	230-230 V
Control gear included	Yes
No dim function	Yes
Beam angle	Medium beam 21-40°
Degree of protection (IP)	IP67
Protection class	I
Max. system power	3 W
Rated luminous flux acc. IEC 62722-2-1	124 lm
Colour of light	White
Colour temperature	3000-3000 K
Colour rendering index CRI	80-89
Height/depth	140 mm
Outer diameter	68 mm
Max. load	2000 kg

Datasheet generated from <https://onetimepim.com> last updated Monday, September 6, 2021 12:41:13 PM

