

3 Years Warranty

L70 25,000hrs

Triac dimmable as standard,
1-10V & DALI dimmable options

Emergency option

Matt White finish



works with

.control


Triac Inline Dimmer
See pg.31



1-10V Inline Dimmer
See pg.35




Smart Rotary Dimmer
See pg.25





On/Off Relay
See pg.37



EN-DLB071D



EN-DLB072D



EN-DLB071D

(H) 50mm Height
(OD) 80mm Overall (Ø)

EN-DLB072D

(H) 65mm Height
(OD) 85mm Overall (Ø)

EN-DLB101D

(H) 60mm Height
(OD) 80mm Overall (Ø)

EN-DLB102D

(H) 80mm Height
(OD) 85mm Overall (Ø)

CurveE™

High output baffled LED downlights

make smart with



See pg.218-219 for compatibility table

Sleek baffled design with the light source recessed back to reduce glare

Aluminium heatsink and bezel

Delivering up to 97lm/W

UGR19 (Unified Glare Rating)

60° beam angle for focused downlighting

IP44 rated

Supplied with remote LED driver



For Dimming Compatibility See pg.224-225



10mm Baffle



20mm Baffle

Cat. No.	Watts	Colour	Lumens	lm/W	Beam	Baffle Recess	Cutout [Ø]
----------	-------	--------	--------	------	------	---------------	------------

Triac Dimmable

EN-DLB071D*/30	7W	3000K	640lm	91	60°	10mm	70mm
EN-DLB071D*/40	7W	4000K	680lm	97	60°	10mm	70mm
EN-DLB072D*/30	7W	3000K	575lm	82	60°	20mm	70mm
EN-DLB072D*/40	7W	4000K	615lm	88	60°	20mm	70mm
EN-DLB101D*/30	10W	3000K	920lm	92	60°	10mm	70mm
EN-DLB101D*/40	10W	4000K	970lm	97	60°	10mm	70mm
EN-DLB102D*/30	10W	3000K	820lm	82	60°	20mm	70mm
EN-DLB102D*/40	10W	4000K	880lm	88	60°	20mm	70mm

Emergency Pack

AU-DLEMB2 3 Hour Maintained Emergency Pack

*Add suffix **DA** or **V** for DALI or 1-10V dimmable options
(note DALI Emergency - the EM side will not report back)



Uni-Fit™

High power integrated LED downlights

make smart with



See pg.218-219 for compatibility table

Featuring ThermoTec™ heat management technology

Delivering up to 93lm/W

Suitable for all new and retrofit installation requirements

Pre-wired with 500mm 2 core cable

IP44 rated

Supplied with integrated LED driver



For Dimming Compatibility see pages 224-225



Downlights

Cat. No.	Watts	Colour	Lumens	lm/W	Beam	Cutout [Ø]
----------	-------	--------	--------	------	------	------------

Non-Dimmable

EN-DL10/30	10W	3000K	850lm	85	100°	90mm
EN-DL10/40	10W	4000K	900lm	90	100°	90mm
EN-DL15/30	15W	3000K	1250lm	83	100°	120mm
EN-DL15/40	15W	4000K	1350lm	90	100°	120mm
EN-DL23/30	23W	3000K	2000lm	87	100°	170mm
EN-DL23/40	23W	4000K	2100lm	91	100°	170mm
EN-DL30/30	30W	3000K	2600lm	87	100°	200mm
EN-DL30/40	30W	4000K	2800lm	93	100°	200mm

Triac Dimmable

EN-DDL10/40	10W	4000K	820lm	82	100°	90mm
EN-DDL15/40	15W	4000K	1200lm	80	100°	120mm
EN-DDL20/40	20W	4000K	1800lm	90	100°	170mm
EN-DDL25/40	25W	4000K	2000lm	80	100°	200mm

Emergency Pack

AU-DLEMB2 3 Hour Maintained Emergency Pack



3 Year Warranty

L70 25,000hrs

Triac dimmable option

Emergency option

White finish

make smart with




works with

.control



Triac Inline Dimmer
See pg.31





Smart Rotary Dimmer
See pg.25



On/Off Relay
See pg.37

EN-DL23



EN-DDL10 (H) 60mm Height (OD) 120mm Overall (Ø)	EN-DL10 (H) 60mm Height (OD) 120mm Overall (Ø)
EN-DDL15 (H) 60mm Height (OD) 150mm Overall (Ø)	EN-DL15 (H) 60mm Height (OD) 150mm Overall (Ø)
EN-DDL20 (H) 65mm Height (OD) 200mm Overall (Ø)	EN-DL23 (H) 65mm Height (OD) 200mm Overall (Ø)
EN-DDL25 (H) 65mm Height (OD) 235mm Overall (Ø)	EN-DL30 (H) 65mm Height (OD) 235mm Overall (Ø)