

Slim-Fit™

Low profile LED downlights




Edge-lit low profile ideal for installations with limited recess space (25mm) and shallow ceiling voids

IP44 rated

Supplied with remote non-dimmable LED driver (40mm void space required)



For Dimming Compatibility See pg.224-225



Ultra slim profile, ideal for shallow ceiling voids

Cat. No.	Watts	Colour	Lumens	lm/W	Beam	Cutout [Ø]	Triac Dimmable Drivers
Non-Dimmable							
EN-PL06B*/30	6W	3000K	300lm	50	110°	107mm	
EN-PL06B*/40	6W	4000K	330lm	55	110°	107mm	EN-PLDD06
EN-PL06B*/65	6W	6500K	350lm	58	110°	107mm	
EN-PL09B*/30	9W	3000K	450lm	50	110°	133mm	
EN-PL09B*/40	9W	4000K	500lm	56	110°	133mm	EN-PLDD09
EN-PL09B*/65	9W	6500K	550lm	61	110°	133mm	
EN-PL12B*/30	12W	3000K	660lm	55	110°	157mm	
EN-PL12B*/40	12W	4000K	780lm	65	110°	157mm	EN-PLDD12
EN-PL12B*/65	12W	6500K	850lm	71	110°	157mm	
EN-PL18B*/30	18W	3000K	1100lm	61	110°	206mm	
EN-PL18B*/40	18W	4000K	1200lm	67	110°	206mm	EN-PLDD18
EN-PL18B*/65	18W	6500K	1300lm	72	110°	206mm	
EN-PL24B*/30	24W	3000K	1450lm	60	110°	280mm	
EN-PL24B*/40	24W	4000K	1600lm	67	110°	280mm	EN-PLDD24
EN-PL24B*/65	24W	6500K	1750lm	73	110°	280mm	

Emergency Pack

EN-PLEM 3 Hour Emergency Pack for Slim-Fit™ Downlights 6W - 12W

EN-DLEM2 3 Hour Emergency Pack for Slim-Fit™ Downlights 18W - 24W

*Add suffix **DA** or **V** for DALI or 1-10V dimmable options (note DALI Emergency - the EM side will not report back)
40mm recess dimensions include required space for the driver



Excluding 6W & 9W

Excluding 6W & 9W

3 Year Warranty

L70 25,000hrs

1-10V, DALI and Triac dimmable options

Emergency option

Matt White finish



works with


.control



Triac In-line Dimmer
See pg.31



1-10V In-line Dimmer
See pg.35





Smart Rotary Dimmer
See pg.25



On/Off Relay
See pg.37

EN-PL18B



EN-PL06B

(H) 25mm Height
(OD) 120mm Overall (Ø)

EN-PL09B

(H) 25mm Height
(OD) 145mm Overall (Ø)

EN-PL12B

(H) 25mm Height
(OD) 174mm Overall (Ø)

EN-PL18B

(H) 25mm Height
(OD) 225mm Overall (Ø)

EN-PL24B

(H) 25mm Height
(OD) 300mm Overall (Ø)

Reflector-Fit™

High powered COB downlight

make smart with



See pg.218-219 for compatibility table

High powered COB downlight with a multi faceted aluminium reflector

Up to 122lm/W

IP44 rated

60° beam angle for maximum light distribution

Supplied with remote triac dimmable LED driver



Downlights



Cat. No.	Watts	Colour	Lumens	lm/W	Beam	Cutout [Ø]
Triac Dimmable						
EN-DDL413*/40	13W	4000K	1480lm	114	60°	120mm
EN-DDL618*/40	18W	4000K	2200lm	122	60°	160mm
EN-DDL818*/40	18W	4000K	2200lm	122	60°	200mm
EN-DDL825*/40	25W	4000K	2890lm	116	60°	200mm
EN-DDL840*/40	40W	4000K	4450lm	111	60°	200mm

Emergency Pack

EN-DLEM2 3 Hour Non-Maintained Emergency Pack

*Add suffix **DA** or **V** for DALI or 1-10V dimmable options (note DALI Emergency - the EM side will not report back)



3 Year Warranty

Triac dimmable as standard, 1-10V & DALI dimmable options

Emergency option

White finish

make smart with



works with


.control



Triac In-Line Dimmer
See pg.31



1-10V In-Line Dimmer
See pg.35





Smart Rotary Dimmer
See pg.25



On/Off Relay
See pg.37

EN-DDL818



EN-DDL413
(H) 65mm Height
(OD) 145mm Overall (Ø)

EN-DDL618
(H) 75mm Height
(OD) 190mm Overall (Ø)

EN-DDL818
(H) 87mm Height
(OD) 225mm Overall (Ø)

EN-DDL825
(H) 87mm Height
(OD) 225mm Overall (Ø)

EN-DDL840
(H) 87mm Height
(OD) 225mm Overall (Ø)