A Market Leader in Form, Function & Reliability



- Convertible design for shallow ceiling void installations down to 47mm
- Insulation coverable, with layover and blown-in insulation
- IP65 and air leakage rated for adjustable, baffle and fixed (with appropriate bezel)
- Fully tested and certified for 30, 60 & 90 minute ceilings, See pg.223 for more information

The most advanced integrated, fire rated downlight on the market expertly designed to prioritise the customer's safety. An evolution on the award winning mSeries[™], the fire rated mPro[™] downlight features NanoDrive[™] Technology with a light output of up to 660lm, with an efficacy of up to 94lm/W and

a LEDchroic[™] lens for halogen-like appearance. Convertible design allows installation in ceiling voids as shallow as 47mm. Interchangeable bezels are universally compatible across the mPro[™] series. Supplied with second generation FastRfix[™] connection system.



5 Year Warranty

L70 40,000hrs

Triac dimmable as standard

Emergency option

White, Matt White, Polished Chrome & Satin Nickel bezel finish options

White slimtrim bezel finish option

Black or White trimless bezel finish options



works with

.control

Triac Inline Dimmer See pg.31



Smart Rotary Dimmer See pg.25







AU-MPR05





AU-MPR01

(H) 100mm Height

(OD) 88mm Overall (Ø)

AU-MPR02

(H) 98mm Height

(OD) 98mm Overall (Ø)

AU-MPR05

(H) 120mm Height (OD) 88mm Overall (Ø)

NPRO

LED fixed/adjustable / baffle fire rated downlights

LEDchroic™ lens provides halogen appearance with LED efficiency, anti-glare and precise beam control

Unique convertible design to fit ceiling voids as shallow as 47mm

Delivering up to 94lm/W

Interchangeable IP65 bezels for fixed version provide a sleek finish

IP65 rated for adjustable and baffle option

SDCM <6 providing consistent light colour quality

FastRFix™ rapid install system connector included - See page 213 for more information

Insulation cover included

60° beam angle for focused downlighting

Tested in 30, 60 and 90-minute fire rated ceilings





Fixed IP65

make rmart with

See pg.218-219 for compatibility table



IP65 Adjustable



IP65 Fixed Baffle



| | Cat. No. | Watts | Colour | Lumens | lm/W | Beam | Cutout [Ø] | |
|--------------------------------------|----------------------------------|------------|------------|--------------|-----------|------|------------|--|
| | mPRO™ Triac Dimm | able Fixed | (IP65 when | used with IP | 65 Bezel) | | | |
| | AU-MPRO1/27 | 7W | 2700K | 560lm | 80 | 60° | 65mm | |
| | AU-MPR01/30 | 7W | 3000K | 600lm | 86 | 60° | 65mm | |
| | AU-MPR01/40 | 7W | 4000K | 640lm | 91 | 60° | 65mm | |
| mPRO™ Triac Dimmable IP65 Adjustable | | | | | | | | |
| | AU-MPR02*/30 | 7W | 3000K | 630lm | 90 | 60° | 85mm | |
| | AU-MPR02*/40 | 7W | 4000K | 660lm | 94 | 60° | 85mm | |
| | mPRO™ Triac Dimmable IP65 Baffle | | | | | | | |
| v | AU-MPR05/30 | 7W | 3000K | 500lm | 71 | 40° | 65mm | |
| v | AU-MPR05/40 | 7W | 4000K | 530lm | 76 | 40° | 65mm | |
| | | | | | | | | |

Bezel Options

AU-BZ600* mPro™ Fixed IP65 Aluminium Downlight Bezel AU-AP600* mPro™ Fixed Fire Rated Adaptor Plate

AU-BZ605W mPro™ Fixed Slimtrim Aluminium Baffle Bezel

NEW AU-MPROTL** mPro™ Fixed Trimless Bezel

*Add suffix W, MW, PC or SN for White, Matt White, Polished Chrome or Satin Nickel finishes.

**Add suffix W or BLK for White or Black finishes. 3 hour Emergency pack AU-FRLM10EM available.











