Kraftform Plus - Series 100 VDE

The safety screwdriver for working with live wiring

162 iS PH VDE Insulated screwdriver with reduced blade diameter for Phillips screws



Application: Phillips screws

Blade: Reduced blade diameter with integrated protective insulation,

allows sunken PH screws to be accessed and actuated,

individually tested as per IEC 60900

Design: Blade zinc-phosphated

Handle: Kraftform with non-roll feature, multi-component. "Take it easy"

tool finder: colour coding according to profile (red = Phillips)

and size stamp.

	•	[]', mm	Û,' mm	[;		
05 006450 001	PH 1	80	98	3 1/8"		
05 006451 001	PH 2	100	105	4"		

162 iSS PH VDE Insulated screwdriver with reduced blade diameter for Phillips screws



Application: Phillips screws

Blade: Reduced blade diameter with integrated protective insulation,

allows sunken PH screws to be accessed and actuated,

individually tested as per IEC 60900

Design: Blade zinc-phosphated

Handle: Kraftform with non-roll feature, multi-component. "Take it easy"

tool finder: colour coding according to profile (red = Phillips)

and size stamp.

	0	[]; mm	Û; mm],
05 020131 001	PH 1	80	81	3 1/8"
05 020133 001	PH 2	100	98	4"

165 i PZ VDE Insulated screwdriver for Pozidriv screws



Application: Suitable for Pozidriv screws

Blade: Insulated, individually tested as per IEC 60900

Design: Lasertip

Handle: Kraftform with non-roll feature, multi-component. "Take it easy"

tool finder: colour coding according to profile (black = Pozidriv)

and size stamp.

	0	[, mm	Û; mm	[;	
05 006160 001 ¹⁾	PZ 0	80	81	3 1/8"	
05 006162 001	PZ 1	80	98	3 1/8"	
05 006163 001	PZ 1	150	98	6"	
05 006164 001	PZ 2	100	105	4"	
05 006165 001	PZ 2	200	105	8"	
05 006166 001	PZ 3	150	112	6"	
05 006168 001 ¹⁾	PZ 4	200	112	8"	

1) without Lasertip

165 i PZ SB VDE Insulated screwdriver for Pozidriv screws

-			4013288
05 100015 001	0	1 x PZ 1x80	181510
05 100016 001	0	1 x PZ 2x100	181527



165 iS PZ VDE Insulated screwdriver with reduced blade diameter for Pozidriv screws



Application: Suitable for Pozidriv screws

Blade: Reduced blade diameter with integrated protective insulation,

allows sunken PZ screws to be accessed and actuated,

individually tested as per IEC 60900

Design: Blade zinc-phosphated

Handle: Kraftform with non-roll feature, multi-component. "Take it easy"

tool finder: colour coding according to profile (black = Pozidriv)

and size stamp.

	0	[]; mm	∯ʻ, mm	[,	
05 006460 001	PZ 1	80	98	3 1/8"	
05 006461 001	PZ 2	100	105	4"	

162 i PH/S VDE Insulated screwdriver for PlusMinus screws (Phillips/slotted)



Application: PlusMinus screws (Phillips/slotted)

Blade: Insulated, individually tested as per IEC 60900

Design: PlusMinus (Phillips/slotted)

Handle: Kraftform with non-roll feature, multi-component

	•	[¦ mm	∯ʻ, mm	[,	
05 006380 001	# 1	80	98	3 1/8"	
05 006381 001	# 2	100	105	4"	

162 i PH/S SB VDE Insulated screwdriver for PlusMinus screws (Phillips/slotted)

			4013288
05 100019 001	0	162 i PH/S VDE	186560
		1 x # 1x80	
05 100020 001	0	162 i PH/S VDE	186577
		1 x # 2x100	



Tip



Screwdrivers "Take it easy"



"Take it easy" tool finder: colour coding according to profile and size stamp. This enables faster and more reliable selection of the correct tool from the tool case.

PlusMinus screwdrivers



For the use in terminal blocks, control cabinets, switches, relays, sockets etc.

Non-roll feature



All Kraftform screwdrivers have a non-roll feature at the lower end of the handle. The hexagonal design prevents any annoying rolling away of the screwdriver at the workplace.