

- Self Test Emergency Light
- 5500k Colour Temperature
- 2 x 15 SMD 2835 LED Lamps
- Polycarbonate Housing & Heads
- Wall Mounted
- \blacksquare Charge and Discharge Protection
- Green LED Indicator
- 3 Hours Emergency Duration
- 9.6V 2200mAH NI-CAD Battery
- BS EN 60598-2-22 Standards
- BS EN 62034 Standards
- Emergency Light Output 535 Lumens
- Dimensions 305 x 306 x 70mm
- Weight 1.85Kg

EMBAT9.6V2200 9.6V 2200mAH Battery



EMST9WNMSPOT

LED IP65 Non Maintained Emergency Twin Spot



- 5500K Colour Temperature
- 2 x 15 SMD 2835 LED Lamp
- Polycarbonate housing & heads
- Ceiling or wall mounted
- Charge and discharge protection
- Green LED Indicator
- 3 Hours Emergency Duration
- 9.6V 2200mAH NI-CAD Battery
- BS EN 60598-2-22 Standards
- Emergency light output 535 Lumens
- Dimensions 305 x 280 x 85mm
- Weight 1.85Kg

EMBAT9.6V2200 9.6V 2200mAH Battery



EM9WNMSPOT2

LED IP65 Non Maintained Emergency Twin Spot