



**Fuse-link, LV, 25 A, AC 550 V, BS88/A1, 14 x 55 mm, gL/gG, BS**



**Part no. 25A 550V AC BS88 FUSE  
NITD25**

Similar to illustration

Product name	Eaton Busmann series low voltage British standard fuse
Part no.	25A 550V AC BS88 FUSE
EAN	5027590504096
Product Length/Depth	55 millimetre
Product height	14 millimetre
Product width	14 millimetre
Product weight	15.7 gram
Compliances	RoHS Compliant CE Marked
Certifications	IEC 60269-2 BS88
Product Tradename	None
Product Type	Low voltage British standard fuse
Product Sub Type	None
Amperage Rating	25 A
Voltage rating	550 V
Voltage type	AC
Breaking capacity	80 kA
Class	Class gG/gL
Application	general industrial applications
Fuse type	NITD
Fuse size	BS88/A1
Fitted with:	Offset bolted tags
Connection	Bolt-on
Suitable for	CM32FC Camaster fuse holder

## Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		A1
Type of current		AC
Rated voltage AC	V	550
Rated voltage DC	V	
Rated current	A	25
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	2
Mounting holes		Other
Centre-to-centre distance of connections	mm	42.5