



Fuse-link, LV, 40 A, AC 500 V, BS88, 21 x 129 mm, gL/gG, BS

BD40

Product name		Eaton Bussmann series low voltage British standard fuse
Part no.		BD40
EAN		5027590492164
Product Length/Depth		129 millimetre
Product height		21 millimetre
Product width		21 millimetre
Product weight		66.9 gram
Compliances		Contact Manufacturer
Product Tradename		None
Product Type		Low voltage British standard fuse
Product Sub Type		None
Amperage Rating		40 A
Voltage rating		500 V
Voltage type		AC
Breaking capacity		80 kA
Class		Class gG/gL
Application		general industrial applications
Fuse type		BD
Fitted with:		Centre bolted tags
Connection		111 mm fixing centre

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ec1@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		Other
Type of current		AC/DC
Rated voltage AC	V	500
Rated voltage DC	V	250
Rated current	A	40
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	4.7
Mounting holes		M8
Centre-to-centre distance of connections	mm	111