



**Fuse-link, LV, 6 A, AC 500 V, 10 x 38 mm, gL/gG, IEC**

**Part no. CYLINDRICAL FUSE 10 x 38 6A GG 500V AC  
C10G6**  
**EL Number 1600254  
(Norway)**

Product name	Eaton Bussmann series low voltage cylindrical fuse
Part no.	CYLINDRICAL FUSE 10 x 38 6A GG 500V AC
EAN	5027590493567
Product Length/Depth	38 millimetre
Product height	10 millimetre
Product width	10 millimetre
Product weight	8.2 gram
Compliances	CE Marked RoHS Compliant GoST-R
Certifications	IEC 60269
Product Tradename	None
Product Type	Low voltage cylindrical fuse
Product Sub Type	None
Amperage Rating	6 A
Voltage rating	500 V
Voltage type	AC
Breaking capacity	120 kA
Utilization category	gG (cable protection/equipment protection)
Suitable for	CHM Modular fuse holder

**Technical data ETIM 8.0**

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015])		
Model		Ceramic fuse
Size		10x38 mm
Voltage type		AC
Rated current	A	6
Rated voltage	V	500
Utilization category		gL/gG (cable protection/equipment protection)
Rated operating frequency	Hz	45 - 62
Type of fuse status indicator		Other
Release characteristic		Other
Breaking capacity	kA	120
Power loss at rated current	W	0.85