

Fuse-link, LV, 50 A, AC 500 V, BS88/A3, 21 x 87 mm, gL/gG, BS



BA050

Similar to illustration

roduct name	Eaton Bussmann series low voltage British standard fuse
rt no.	BA050
N.	5027590491983
duct Length/Depth	87 millimetre
oduct height	22.3 millimetre
oduct width	21 millimetre
oduct weight	53.2 gram
ompliances	Contact Manufacturer
roduct Tradename	None
roduct Type	Low voltage British standard fuse
roduct Sub Type	None
mperage Rating	50 A
oltage rating	500 V
ltage type	AC
eaking capacity	80 kA
ass	Class gG/gL
pplication	general industrial applications
ise type	BAO
use size	BS88/A3
itted with:	Offset bolted tags
onnection	74 mm Fixing Centre
itable for	CM63F Camaster fuse holder RS63 Red spot fuse holder

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011]) Fuse construction type according to IEC 60269 А3 AC Type of current Rated voltage AC ٧ 500 Rated voltage DC ٧ Rated current Α 50 Utilization category gL/gG (cable protection/equipment protection) Breaking capacity kA 80 None Colour code Type of fuse status indicator None W Power loss at rated current 4.9 M5 Mounting holes Centre-to-centre distance of connections 73.5 mm