

Fuse-link, LV, 10 A, AC 240 V, BS88/E1, 12 \times 47 mm, gL/gG, BS



SSD10

| Product name | Eaton Bussmann series low voltage British standard fuse |
|----------------------|---|
| Part no. | SSD10 |
| EAN | 5027590511735 |
| Product Length/Depth | 47 millimetre |
| Product height | 12 millimetre |
| Product width | 12 millimetre |
| Product weight | 10 gram |
| Compliances | CE Marked RoHS Compliant |
| Certifications | BS88 IEC 60269-2 |
| Product Tradename | None |
| Product Type | Low voltage British standard fuse |
| Product Sub Type | None |
| | |
| Amperage Rating | 10 A |
| Voltage rating | 240 V |
| Voltage type | AC |
| Breaking capacity | 33 kA |
| Class | Class gG/gL |
| | |
| Application | street lighting cut-outs |
| Fuse type | SSD |
| Fuse size | BS88/E1 |
| Fitted with: | Offset bladed tags |
| Connection | Blade end |
| Suitable for | SC20 Safeclip fuse holder |

Technical data ETIM 8.0

| Circuit breakers and fuses (EG000020) / HRC fuse (EC004556) | | | | |
|--|--|----|---|--|
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011]) | | | | |
| Fuse construction type according to IEC 60269 | | | E1 | |
| Type of current | | | AC | |
| Rated voltage AC | | V | 240 | |
| Rated voltage DC | | V | | |
| Rated current | | Α | 10 | |
| Utilization category | | | gL/gG (cable protection/equipment protection) | |
| Breaking capacity | | kA | 33 | |
| Colour code | | | None | |
| Type of fuse status indicator | | | None | |
| Power loss at rated current | | W | 1.2 | |
| Mounting holes | | | | |
| Centre-to-centre distance of connections | | mm | | |