## Fuse-link, LV, 40 A, AC 415 V, BS88/F2, 18 x 68 mm, gL/gG, BS



## ESD40

Similar to illustration

Product name	Eaton Bussmann series low voltage British standard fuse
Part no.	ESD40
EAN	5027590498661
Product Length/Depth	67 millimetre
Product height	18 millimetre
Product width	18 millimetre
Product weight	30.5 gram
Compliances	Contact Manufacturer
Product Tradename	None
Product Type	Low voltage British standard fuse
Product Sub Type	None
Amperage Rating	40 A
Voltage rating	415 V
Voltage type	AC
Breaking capacity	80 kA
Class	Class gG/gL
Application	general industrial applications
Fuse type	ESD
Fuse size	BS88/F2
Fitted with:	Offset bladed tags
Connection	Blade end
Suitable for	63ENS Safeloc fuse holder SC63 Safeclip fuse holder

## **Technical data ETIM 8.0**

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical i	installation, device / Safe	ety fuse ir	nserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])
Fuse construction type according to IEC 60269			F2
Type of current			AC
Rated voltage AC	1	V	415
Rated voltage DC	1	V	
Rated current	,	Α	40
Utilization category			gL/gG (cable protection/equipment protection)
Breaking capacity	i	kA	80
Colour code			None
Type of fuse status indicator			None
Power loss at rated current	١	W	3.2
Mounting holes			
Centre-to-centre distance of connections	1	mm	