

SMD16

| | | |
|----------------------|--|---|
| Product name | | Eaton Bussmann series low voltage British standard fuse |
| Part no. | | SMD16 |
| EAN | | 5027590510998 |
| Product Length/Depth | | 29 millimetre |
| Product height | | 16 millimetre |
| Product width | | 16 millimetre |
| Product weight | | 12.1 gram |
| Compliances | | RoHS Compliant CE Marked |
| Certifications | | IEC 60269 EAC BS88 |
| Product Tradename | | None |
| Product Type | | Low voltage British standard fuse |
| Product Sub Type | | None |
| Amperage Rating | | 16 A |
| Voltage rating | | 415 V |
| Voltage type | | AC |
| Breaking capacity | | 80 kA |
| Class | | Class gG/gL |
| Application | | street lighting cut-outs |
| Fuse type | | SMD |
| Connection | | Ferrule end x ferrule end |

Technical data ETIM 8.0

| | | |
|--|----|---|
| Circuit breakers and fuses (EG000020) / HRC fuse (EC004556) | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011]) | | |
| Fuse construction type according to IEC 60269 | | Other |
| Type of current | | AC |
| Rated voltage AC | V | 415 |
| Rated voltage DC | V | |
| Rated current | A | 16 |
| Utilization category | | gL/gG (cable protection/equipment protection) |
| Breaking capacity | kA | 80 |
| Colour code | | None |
| Type of fuse status indicator | | None |
| Power loss at rated current | W | 1.8 |
| Mounting holes | | |
| Centre-to-centre distance of connections | mm | |