

## Fuse-link, LV, 6 A, AC 550 V, BS88/A2, 14 x 85 mm, gL/gG, BS



## **AA06**

Product name	Eaton Bussmann series low voltage British standard fuse
Part no.	AA06
EAN	5027590491624
Product Length/Depth	85 millimetre
Product height	14 millimetre
Product width	14 millimetre
Product weight	20.1 gram
Compliances	CE Marked RoHS Compliant
Certifications	IEC 60269-2 BS88
Product Tradename	None
Product Type	Low voltage British standard fuse
Product Sub Type	None
Amperage Rating	6 A
/oltage rating	550 V
/oltage type	AC
Breaking capacity	80 kA
Class	Class gG/gL
Application	general industrial applications
use type	AAO
-use size	BS88/A2
Fitted with:	Offset bolted tags
Connection	73 mm fixing centre
Quantity	20
Suitable for	CM32F Camaster fuse holder RS32 Red spot fuse holder

## **Technical data ETIM 8.0**

166111116a1 uata ETTIVI 0.0			
Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installa	ition, device / Sa	fety fuse i	nserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])
Fuse construction type according to IEC 60269			A2
Type of current			AC
Rated voltage AC		V	550
Rated voltage DC		V	
Rated current		Α	6
Utilization category			gL/gG (cable protection/equipment protection)
Breaking capacity		kA	80
Colour code			None
Type of fuse status indicator			None
Power loss at rated current		W	1.8
Mounting holes			
Centre-to-centre distance of connections		mm	73