



Fuse-link, LV, 20 A, AC 550 V, BS88/A1, 14 x 55 mm, gL/gG, BS

NITD20

Similar to illustration

| | | |
|----------------------|--|--|
| Product name | Eaton Bussmann series low voltage British standard fuse | |
| Part no. | NITD20 | |
| EAN | 5027590504034 | |
| Product Length/Depth | 55 millimetre | |
| Product height | 14 millimetre | |
| Product width | 14 millimetre | |
| Product weight | 15.75 gram | |
| Compliances | RoHS Compliant CE Marked | |
| Certifications | BS88 IEC 60269-2 | |
| Product Tradename | None | |
| Product Type | Low voltage British standard fuse | |
| Product Sub Type | None | |
| Amperage Rating | 20 A | |
| Voltage rating | 550 V | |
| Voltage type | AC | |
| Breaking capacity | 80 kA | |
| Class | Class gG/gL | |
| Application | general industrial applications | |
| Fuse type | NITD | |
| Fuse size | BS88/A1 | |
| Fitted with: | Offset bolted tags | |
| Connection | Bolt-on | |
| Suitable for | CM32FC Camaster fuse holder RS20 Red spot fuse holder | |

Technical data ETIM 8.0

| | | |
|--|----|---|
| Circuit breakers and fuses (EG000020) / HRC fuse (EC004556) | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011]) | | |
| Fuse construction type according to IEC 60269 | | A1 |
| Type of current | | AC |
| Rated voltage AC | V | 550 |
| Rated voltage DC | V | |
| Rated current | A | 20 |
| Utilization category | | gL/gG (cable protection/equipment protection) |
| Breaking capacity | kA | 80 |
| Colour code | | None |
| Type of fuse status indicator | | None |
| Power loss at rated current | W | 1.8 |
| Mounting holes | | Other |
| Centre-to-centre distance of connections | mm | 42.5 |