



Fuse-link, LV, 63 A, AC 500 V, BS88, 21 x 129 mm, gL/gG, BS

BD63

Product name		Eaton Bussmann series low voltage British standard fuse
Part no.		BD63
EAN		5027590492188
Product Length/Depth		129 millimetre
Product height		21 millimetre
Product width		21 millimetre
Product weight		66.9 gram
Compliances		CE Marked RoHS Compliant
Certifications		BS88 IEC 60269-2
Product Tradename		None
Product Type		Low voltage British standard fuse
Product Sub Type		None
Amperage Rating		63 A
Voltage rating		500 V
Voltage type		AC
Breaking capacity		80 kA
Class		Class gG/gL
Application		general industrial applications
Fuse type		BD
Fitted with:		Centre bolted tags
Connection		111 mm fixing centre

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		Other
Type of current		AC/DC
Rated voltage AC	V	500
Rated voltage DC	V	250
Rated current	A	63
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	5.6
Mounting holes		M8
Centre-to-centre distance of connections	mm	111