

ESD32

Similar to illustration

| | |
|----------------------|---|
| Product name | Eaton Bussmann series low voltage British standard fuse |
| Part no. | ESD32 |
| EAN | 5027590498647 |
| Product Length/Depth | 67 millimetre |
| Product height | 14 millimetre |
| Product width | 14 millimetre |
| Product weight | 30.5 gram |
| Compliances | Contact Manufacturer |
| Product Tradename | None |
| Product Type | Low voltage British standard fuse |
| Product Sub Type | None |
| Amperage Rating | 32 A |
| Voltage rating | 550 V |
| Voltage type | AC |
| Breaking capacity | 80 kA |
| Class | Class gG/gL |
| Application | general industrial applications |
| Fuse type | ESD |
| Fuse size | BS88/F2 |
| Fitted with: | Offset bladed tags |
| Connection | Blade end |
| Suitable for | 63ENS Safelec fuse holder SC63 Safeclip fuse holder |

Technical data ETIM 8.0

| | | |
|--|----|---|
| Circuit breakers and fuses (EG000020) / HRC fuse (EC004556) | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011]) | | |
| Fuse construction type according to IEC 60269 | | F2 |
| Type of current | | AC |
| Rated voltage AC | V | 550 |
| Rated voltage DC | V | |
| Rated current | A | 32 |
| Utilization category | | gL/gG (cable protection/equipment protection) |
| Breaking capacity | kA | 80 |
| Colour code | | None |
| Type of fuse status indicator | | None |
| Power loss at rated current | W | 2.9 |
| Mounting holes | | |
| Centre-to-centre distance of connections | mm | |