Fuse-link, LV, 32 A, AC 415 V, BS88/A1, 18 x 55 mm, gM, BS, 32M50



NITD32M50

Similar to illustration

duct name	Eaton Bussmann series low voltage British standard fuse
Part no.	NITD32M50
EAN .	5027590504140
Product Length/Depth	57 millimetre
Product height	18 millimetre
Product width	18 millimetre
Product weight	27.15 gram
Compliances	RoHS Compliant CE Marked
Certifications	BS88 EAC IEC 60269
Product Tradename	None
Product Type	Low voltage British standard fuse
Product Sub Type	None
Amperage Rating	32 A
oltage rating	415 V
/oltage type	AC
Breaking capacity	80 kA
Class	Class gM
Application	general industrial applications
use type	NITD
use size	BS88/A1
Fitted with:	Offset bolted tags
Connection	Bolt-on
Suitable for	CM32FC Camaster fuse holder

Technical data ETIM 8.0

Toomitour data ETTIT OIO			
Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installati	on, device / Safet	ty fuse ir	nserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])
Fuse construction type according to IEC 60269			A1
Type of current			AC
Rated voltage AC	٧	/	415
Rated voltage DC	V	/	
Rated current	A	4	32
Utilization category			gM (motor protection)
Breaking capacity	k	κA	80
Colour code			None
Type of fuse status indicator			None
Power loss at rated current	V	W	1.4
Mounting holes			M10
Centre-to-centre distance of connections	n	mm	42.5