



Fuse-link, LV, 50 A, AC 415 V, BS88/F2, 18 x 68 mm, gL/gG, BS

ESD50

Product name		Eaton Bussmann series low voltage British standard fuse
Part no.		ESD50
EAN		5027590498678
Product Length/Depth		67 millimetre
Product height		18 millimetre
Product width		18 millimetre
Product weight		29.85 gram
Compliances		RoHS Compliant CE Marked
Certifications		BS88 IEC 60269-2
Product Tradename		None
Product Type		Low voltage British standard fuse
Product Sub Type		None
Amperage Rating		50 A
Voltage rating		415 V
Voltage type		AC
Breaking capacity		80 kA
Class		Class gG/gL
Application		general industrial applications
Fuse type		ESD
Fuse size		BS88/F2
Fitted with:		Offset bladed tags
Connection		Blade end
Suitable for		63ENS Safeloc fuse holder SC63 Safeclip fuse holder

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		F2
Type of current		AC
Rated voltage AC	V	415
Rated voltage DC	V	
Rated current	A	50
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	3.9
Mounting holes		
Centre-to-centre distance of connections	mm	