

Fuse-link, LV, 80 A, AC 500 V, BS88/B1, 21 x 126 mm, gL/gG, BS



CD80

oduct name	Eaton Bussmann series low voltage British standard fuse
art no.	CD80
AN	5027590496230
oduct Length/Depth	127 millimetre
oduct height	21 millimetre
oduct width	21 millimetre
oduct weight	80.2 gram
ompliances	RoHS Compliant CE Marked
ertifications	BS88 EAC IEC 60269
oduct Tradename	None
oduct Type	Low voltage British standard fuse
oduct Sub Type	None
nperage Rating	80 A
ltage rating	500 V
oltage type	AC
eaking capacity	80 kA
ass	Class gG/gL
pplication	general industrial applications
se type	CD
se size	BS88/B1
ted with:	Centre bolted tags
onnection	111 mm fixing centre

Technical data ETIM 8.0

1001111041 4414 211111 010			
Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installation	on, device / Safety	y fuse in	serts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])
Fuse construction type according to IEC 60269			B1
Type of current			AC
Rated voltage AC	V		500
Rated voltage DC	V		
Rated current	А		80
Utilization category			gL/gG (cable protection/equipment protection)
Breaking capacity	k <i>A</i>	A	80
Colour code			None
Type of fuse status indicator			None
Power loss at rated current	W	/	7.2
Mounting holes			M8
Centre-to-centre distance of connections	m	ım	111