

## DE0125

Similar to illustration

|                      |  |   |
|----------------------|--|---|
| Product name         |  | Eaton Bussmann series low voltage British standard fuse |
| Part no.             |  | DE0125  |
| EAN                  |  | 5027590497770   |
| Product Length/Depth |  | 110 millimetre  |
| Product height       |  | 29.5 millimetre   |
| Product width        |  | 31 millimetre   |
| Product weight       |  | 144.4 gram  |
| Compliances          |  | RoHS Compliant  |
| Product Tradename    |  | None  |
| Product Type         |  | Low voltage British standard fuse                       |
| Product Sub Type     |  | None  |
| Amperage Rating      |  | 25 A  |
| Voltage rating       |  | 415 V   |
| Voltage type         |  | AC  |
| Breaking capacity    |  | 80 kA   |
| Class                |  | Class gG/gL   |
| Application          |  | general industrial applications                         |
| Fuse type            |  | DE0   |
| Fitted with:         |  | Offset bolted tags                                      |
| Connection           |  | 94 mm fixing centre                                     |

## Technical data ETIM 8.0

|  |    |   |
|--|----|---|
| Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)  |    |   |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011]) |    |   |
| Fuse construction type according to IEC 60269  |    | Other   |
| Type of current  |    | AC  |
| Rated voltage AC   | V  | 415   |
| Rated voltage DC   | V  |   |
| Rated current  | A  | 25  |
| Utilization category   |    | gL/gG (cable protection/equipment protection) |
| Breaking capacity  | kA | 80  |
| Colour code  |    | None  |
| Type of fuse status indicator  |    | None  |
| Power loss at rated current  | W  | 11  |
| Mounting holes   |    | M8  |
| Centre-to-centre distance of connections   | mm | 93.7  |