



Fuse-link, low voltage, AC 415 V, BS88/F2, 21 x 68 mm, gM, BS

ESD63M100

Similar to illustration

Product name	Eaton Bussmann series low voltage British standard fuse	
Part no.	ESD63M100	
EAN	5027590498708	
Product Length/Depth	67 millimetre	
Product height	22 millimetre	
Product width	22 millimetre	
Product weight	42.1 gram	
Compliances	Contact Manufacturer	
Product Tradename	None	
Product Type	Low voltage British standard fuse	
Product Sub Type	None	
Amperage Rating	63 A	
Voltage rating	415 V	
Voltage type	AC	
Breaking capacity	80 kA	
Class	Class gM	
Application	general industrial applications	
Fuse type	ESD	
Fuse size	BS88/F2	
Fitted with:	Offset bladed tags	
Connection	Blade end	
Suitable for	63ENS Safelec fuse holder SC63 Safeclip fuse holder	

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		F2
Type of current		AC
Rated voltage AC	V	415
Rated voltage DC	V	
Rated current	A	63
Utilization category		gM (motor protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	2.5
Mounting holes		
Centre-to-centre distance of connections	mm	