



Fuse-link, LV, 250 A, AC 415 V, BS88/B2, 31 x 158 mm, gL/gG, BS

EFS250

Similar to illustration

| | | |
|----------------------|---|--|
| Product name | Eaton Bussmann series low voltage British standard fuse | |
| Part no. | EFS250 | |
| EAN | 5027590019071 | |
| Product Length/Depth | 209 millimetre | |
| Product height | 39 millimetre | |
| Product width | 39 millimetre | |
| Product weight | 180 gram | |
| Compliances | RoHS Compliant | |
| Product Tradename | None | |
| Product Type | Low voltage British standard fuse | |
| Product Sub Type | None | |
| Amperage Rating | 250 A | |
| Voltage rating | 415 V | |
| Voltage type | AC | |
| Breaking capacity | 80 kA | |
| Class | Class gG/gL | |
| Application | general industrial applications | |
| Fuse type | EFS | |
| Fitted with: | Centre bolted tags | |
| Connection | 133 mm fixing centre | |

Technical data ETIM 8.0

| | | |
|--|----|---|
| Circuit breakers and fuses (EG000020) / HRC fuse (EC004556) | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011]) | | |
| Fuse construction type according to IEC 60269 | | B2 |
| Type of current | | AC |
| Rated voltage AC | V | 415 |
| Rated voltage DC | V | |
| Rated current | A | 250 |
| Utilization category | | gL/gG (cable protection/equipment protection) |
| Breaking capacity | kA | 80 |
| Colour code | | None |
| Type of fuse status indicator | | None |
| Power loss at rated current | W | 18 |
| Mounting holes | | |
| Centre-to-centre distance of connections | mm | 133 |