



Fuse-link, LV, 16 A, AC 550 V, BS88/F2, 14 x 68 mm, gL/gG, BS

ESD16

Product name		Eaton Bussmann series low voltage British standard fuse
Part no.		ESD16
EAN		5027590498609
Product Length/Depth		67 millimetre
Product height		15 millimetre
Product width		15 millimetre
Product weight		30.5 gram
Compliances		CE Marked RoHS Compliant
Certifications		BS88 EAC IEC 60269
Product Tradename		None
Product Type		Low voltage British standard fuse
Product Sub Type		None
Amperage Rating		16 A
Voltage rating		550 V
Voltage type		AC
Breaking capacity		80 kA
Class		Class gG/gL
Application		general industrial applications
Fuse type		ESD
Fuse size		BS88/F2
Fitted with:		Offset bladed tags
Connection		Blade end
Suitable for		63ENS Safelec fuse holder SC63 Safeclip fuse holder

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		F2
Type of current		AC
Rated voltage AC	V	550
Rated voltage DC	V	
Rated current	A	16
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	1.8
Mounting holes		
Centre-to-centre distance of connections	mm	