

Fuse-link, LV, 63 A, AC 500 V, BS88/A4, 25 x 110 mm, gL/gG, BS



CEO63

Similar to illustration

oduct name	Eaton Bussmann series low voltage British standard fuse
rt no.	CE063
N	5027590496315
oduct Length/Depth	109.5 millimetre
oduct height	24.5 millimetre
oduct width	21 millimetre
oduct weight	77.6 gram
mpliances	Contact Manufacturer
oduct Tradename	None
oduct Type	Low voltage British standard fuse
oduct Sub Type	None
nperage Rating	63 A
Itage rating	500 V
Itage type	AC
eaking capacity	80 kA
iss	Class gG/gL
plication	general industrial applications
se type	CEO
se size	BS88/A4
ted with:	Offset bolted tags
nnection	94 mm fixing centre
itable for	RS100 Red spot fuse holder

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installat	tion, device / Saf	ety fuse ii	nserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])
Fuse construction type according to IEC 60269			A4
Type of current			AC
Rated voltage AC		V	500
Rated voltage DC		V	
Rated current		Α	63
Utilization category			gL/gG (cable protection/equipment protection)
Breaking capacity		kA	80
Colour code			None
Type of fuse status indicator			None
Power loss at rated current		W	5.6
Mounting holes			M8
Centre-to-centre distance of connections		mm	94