



House service fuse-link, low voltage, 100 A, AC 415 V, BS system C type II, 23 x 57 mm, gL/gG, BS



100KR85

Product name		Eaton Bussmann series low voltage British standard fuse
Part no.		100KR85
EAN		5027590427746
Product Length/Depth		57 millimetre
Product height		22.2 millimetre
Product width		22.2 millimetre
Product weight		55.5 gram
Compliances		RoHS Compliant CE Marked
Certifications		BS IEC 60269
Product Tradename		None
Product Type		Low voltage British standard fuse
Product Sub Type		None
Amperage Rating		100 A
Voltage rating		415 V
Voltage type		AC
Breaking capacity		33 kA
Class		Class gG/gL
Application		protection of incoming cables into residential and commercial properties
Fuse type		KR85
Connection		Ferrule end x ferrule end

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecI@ss10.0.1-27-14-20-01 [AFZ796015])		
Model		Ceramic fuse
Size		23x57 mm
Voltage type		AC
Rated current	A	100
Rated voltage	V	415
Utilization category		gL/gG (cable protection/equipment protection)
Rated operating frequency	Hz	45 - 62
Type of fuse status indicator		Other
Release characteristic		Other
Breaking capacity	kA	33
Power loss at rated current	W	6.1