



House service fuse-link, LV, 60 A, AC 415 V, BS system C type II, 23 x 57 mm, gL/gG, BS

60LR85

Product name	Eaton Bussmann series low voltage British standard fuse
Part no.	60LR85
EAN	5027590484480
Product Length/Depth	56 millimetre
Product height	31 millimetre
Product width	31 millimetre
Product weight	100.5 gram
Compliances	CE Marked RoHS Compliant
Certifications	BS IEC 60269
Product Tradename	None
Product Type	Low voltage British standard fuse
Product Sub Type	None
Amperage Rating	60 A
Voltage rating	415 V
Voltage type	AC
Breaking capacity	33 kA
Class	Class gG/gL
Application	protection of incoming cables into residential and commercial properties
Fuse type	LR85
Connection	Ferrule end x ferrule end

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)	
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecI@ss10.0.1-27-14-20-01 [AFZ796015])	
Model	Ceramic fuse
Size	23x57 mm
Voltage type	AC
Rated current	A 60
Rated voltage	V 415
Utilization category	gL/gG (cable protection/equipment protection)
Rated operating frequency	Hz 45 - 62
Type of fuse status indicator	Other
Release characteristic	Other
Breaking capacity	kA 33
Power loss at rated current	W 4.5