



Fuse-link, LV, 40 A, AC 500 V, BS88/A3, 21 x 87 mm, gL/gG, BS

BA040

Product name		Eaton Bussmann series low voltage British standard fuse
Part no.		BA040
EAN		5027590491976
Product Length/Depth		87 millimetre
Product height		21 millimetre
Product width		21 millimetre
Product weight		50.4 gram
Compliances		RoHS Compliant CE Marked
Certifications		BS88 IEC 60269-2
Product Tradename		None
Product Type		Low voltage British standard fuse
Product Sub Type		None
Amperage Rating		40 A
Voltage rating		500 V
Voltage type		AC
Breaking capacity		80 kA
Class		Class gG/gL
Application		general industrial applications
Fuse type		BA0
Fuse size		BS88/A3
Fitted with:		Offset bolted tags
Connection		74 mm Fixing Centre
Suitable for		CM63F Camaster fuse holder RS63 Red spot fuse holder

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		A3
Type of current		AC
Rated voltage AC	V	500
Rated voltage DC	V	
Rated current	A	40
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	4.7
Mounting holes		M5
Centre-to-centre distance of connections	mm	73.5