Fuse-link, LV, 6 A, AC 240 V, BS88/E1, 12 x 47 mm, gL/gG, BS



Part no. 6A 240V AC INDUSTRIAL FUSE SSD6

Similar to illustration

Product name	Eaton Bussmann series low voltage British standard fuse
Part no.	6A 240V AC INDUSTRIAL FUSE
EAN	5027590511827
Product Length/Depth	47 millimetre
Product height	12 millimetre
Product width	12 millimetre
Product weight	10.9 gram
Compliances	RoHS Compliant CE Marked
Product Tradename	None
Product Type	Low voltage British standard fuse
Product Sub Type	None
Amperage Rating	6 A
/oltage rating	240 V
/oltage type	AC
Breaking capacity	33 kA
Class	Class gG/gL
Application	street lighting cut-outs
use type	SSD
use size	BS88/E1
itted with:	Offset bladed tags
Connection	Blade end
Suitable for	SC20 Safeclip fuse holder

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrica	al installation, device / Safety	y fuse ir	nserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])
Fuse construction type according to IEC 60269			E1
Type of current			AC
Rated voltage AC	V	,	240
Rated voltage DC	V	,	
Rated current	Α	١.	6
Utilization category			gL/gG (cable protection/equipment protection)
Breaking capacity	k/	Α	33
Colour code			None
Type of fuse status indicator			None
Power loss at rated current	W	V	1.6
Mounting holes			
Centre-to-centre distance of connections	m	nm	