Fuse-link, LV, 25 A, AC 240 V, BS88/E1, 12 \times 47 mm, gL/gG, BS



SSD25

Similar to illustration

Product name	Eaton Bussmann series low voltage British standard fuse
Part no.	SSD25
EAN	5027590511797
Product Length/Depth	47 millimetre
Product height	12 millimetre
Product width	12 millimetre
Product weight	11.6 gram
Compliances	RoHS Compliant CE Marked
Product Tradename	None
Product Type	Low voltage British standard fuse
Product Sub Type	None
Amperage Rating	25 A
Voltage rating	240 V
Voltage type	AC
Breaking capacity	33 kA
Class	Class gG/gL
Application	street lighting cut-outs
Fuse type	SSD
Fuse size	BS88/E1
Fitted with:	Offset bladed tags
Connection	Blade end
Suitable for	SC20 Safeclip fuse holder

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrica	l installation, device / Safety f	y fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB2640
Fuse construction type according to IEC 60269		E1
Type of current		AC
Rated voltage AC	V	240
Rated voltage DC	V	
Rated current	А	25
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	A 33
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	V 1.8
Mounting holes		
Centre-to-centre distance of connections	mm	nm