



**Fuse-link, LV, 20 A, AC 550 V, BS88/A2, 14 x 85 mm, gL/gG, BS**



**Part no. 20A 550V AC BS88 gG REF A2 FUSE  
AA020**

Similar to illustration

Product name	Eaton Bussmann series low voltage British standard fuse
Part no.	20A 550V AC BS88 gG REF A2 FUSE
EAN	5027590491532
Product Length/Depth	85 millimetre
Product height	14 millimetre
Product width	14 millimetre
Product weight	20.1 gram
Compliances	RoHS Compliant
Product Tradename	None
Product Type	Low voltage British standard fuse
Product Sub Type	None
Amperage Rating	20 A
Voltage rating	550 V
Voltage type	AC
Breaking capacity	80 kA
Class	Class gG/gL
Application	general industrial applications
Fuse type	AA0
Fuse size	BS88/A2
Fitted with:	Offset bolted tags
Connection	73 mm fixing centre
Quantity	20
Suitable for	CM32F Camaster fuse holder RS32 Red spot fuse holder

### Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		A2
Type of current		AC
Rated voltage AC	V	550
Rated voltage DC	V	
Rated current	A	20
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	1.9
Mounting holes		
Centre-to-centre distance of connections	mm	73