



Fuse-link, LV, 50 A, AC 500 V, BS88/A4, 25 x 110 mm, gL/gG, BS

CE050

Product name		Eaton Bussmann series low voltage British standard fuse
Part no.		CE050
EAN		5027590496308
Product Length/Depth		109.5 millimetre
Product height		24.5 millimetre
Product width		21 millimetre
Product weight		77.6 gram
Compliances		RoHS Compliant CE Marked
Certifications		IEC 60269-2 BS88
Product Tradename		None
Product Type		Low voltage British standard fuse
Product Sub Type		None
Amperage Rating		50 A
Voltage rating		500 V
Voltage type		AC
Breaking capacity		80 kA
Class		Class gG/gL
Application		general industrial applications
Fuse type		CEO
Fuse size		BS88/A4
Fitted with:		Offset bolted tags
Connection		94 mm fixing centre
Suitable for		RS100 Red spot fuse holder

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		A4
Type of current		AC
Rated voltage AC	V	500
Rated voltage DC	V	
Rated current	A	50
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	4.9
Mounting holes		M8
Centre-to-centre distance of connections	mm	94