



Fuse-link, high speed, 16 A, AC 240 V, DC 150 V, BS88, 9 x 47 mm, aR, BS



**16LCT**

Similar to illustration

Product name	Eaton Bussmann series high speed British standard fuse
Part no.	16LCT
EAN	5027590437653
Product Length/Depth	47 millimetre
Product height	9 millimetre
Product width	9 millimetre
Product weight	5.8 gram
Compliances	RoHS Compliant CE Marked
Certifications	IEC Rated UL Recognized CCC IEC 60269-4 UL recognized Designed and tested to BS88 part 4
Product Tradename	None
Product Type	High speed British standard fuse
Product Sub Type	None
Amperage Rating	16 A
Voltage rating	240 Vac, 150 Vdc
Rated voltage AC	240 V
Rated voltage DC	150 V
Interrupt rating	200 kA RMS Sym, 50 kA DC at 150 Vdc
Class	Class aR
Clearing (I2T)	100
Watt losses	2.5 W
Application	Semiconductor, DC Common bus, DC drives, power converters/rectifiers
Fuse indicator	None
Suitable for	T1250 Fuse indicator MAI Microswitch/adaptor MBI Microswitch/adaptor

**Technical data ETIM 8.0**

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		Other
Type of current		AC/DC
Rated voltage AC	V	240
Rated voltage DC	V	150
Rated current	A	16
Utilization category		aR (accompanied semiconductor protection)
Breaking capacity	kA	200
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	2.5
Mounting holes		M6

