



Fuse-link, LV, 100 A, AC 415 V, BS88/A4, 27 x 110 mm, gM, BS, 100M125

CE0100M125

Product name		Eaton Bussmann series low voltage British standard fuse
Part no.		CE0100M125
EAN		5027590496254
Product Length/Depth		111 millimetre
Product height		28 millimetre
Product width		28 millimetre
Product weight		102.4 gram
Compliances		Contact Manufacturer
Product Tradename		None
Product Type		Low voltage British standard fuse
Product Sub Type		None
Amperage Rating		125 A
Voltage rating		415 V
Voltage type		AC
Breaking capacity		80 kA
Class		Class gM
Application		general industrial applications
Fuse type		CEO
Fuse size		BS88/A4
Fitted with:		Offset bolted tags
Connection		94 mm fixing centre
Suitable for		RS100 Red spot fuse holder

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		A4
Type of current		AC
Rated voltage AC	V	415
Rated voltage DC	V	
Rated current	A	125
Utilization category		gM (motor protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	6.5
Mounting holes		M8
Centre-to-centre distance of connections	mm	93.5