

NSD32M50

Similar to illustration

Product name		Eaton Bussmann series low voltage British standard fuse
Part no.		NSD32M50
EAN		5027590504911
Product Length/Depth		59 millimetre
Product height		18 millimetre
Product width		18 millimetre
Product weight		26.8 gram
Compliances		RoHS Compliant
Product Tradename		None
Product Type		Low voltage British standard fuse
Product Sub Type		None
Amperage Rating		50 A
Voltage rating		415 V
Voltage type		AC
Breaking capacity		80 kA
Class		Class gM
Application		general industrial applications
Fuse type		NSD
Fuse size		BS88/F1
Fitted with:		Offset bladed tags
Connection		Blade end
Suitable for		32NNS Safeloc fuse holder SC32 Safeclip fuse holder

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		F2
Type of current		AC
Rated voltage AC	V	415
Rated voltage DC	V	
Rated current	A	50
Utilization category		gM (motor protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	1.4
Mounting holes		
Centre-to-centre distance of connections	mm	