

House service fuse-link, low voltage, 20 A, AC 415 V, BS system C type II, 23 x 57 mm, gL/gG, BS



20KR85

Product name	Eato	n Bussmann series low voltage British standard fuse
Part no.	20KR	385
EAN	5027	590467919
Product Length/Depth	56 m	illimetre
Product height	23 m	illimetre
Product width	23 m	illimetre
Product weight	53.45	5 gram
Compliances		S Compliant Narked
Certifications	IEC 6 BS	60269
Product Tradename	None	e
Product Type	Low	voltage British standard fuse
Product Sub Type	None	e
Amperage Rating	20 A	
Voltage rating	415 \	V
Voltage type	AC	
Breaking capacity	33 kA	A
Class	Class	s gG/gL
Application	prote	ection of incoming cables into residential and commercial properties
Fuse type	KR85	5
Connection	Ferru	ule end x ferrule end

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)				
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015])				
Model			Ceramic fuse	
Size			23x57 mm	
Voltage type			AC	
Rated current	А		20	
Rated voltage	V	,	415	
Utilization category			gL/gG (cable protection/equipment protection)	
Rated operating frequency	Н	z	45 - 62	
Type of fuse status indicator			Other	
Release characteristic			Other	
Breaking capacity	k	A	33	
Power loss at rated current	W	V	2.6	