



Fuse-link, LV, 2 A, AC 550 V, BS88/F1, 14 x 59 mm, gL/gG, BS

NSD2

Product name		Eaton Bussmann series low voltage British standard fuse
Part no.		NSD2
EAN		5027590504805
Product Length/Depth		60 millimetre
Product height		14 millimetre
Product width		14 millimetre
Product weight		16.2 gram
Compliances		CE Marked RoHS Compliant
Certifications		IEC 60269-2 BS88
Product Tradename		None
Product Type		Low voltage British standard fuse
Product Sub Type		None
Amperage Rating		2 A
Voltage rating		550 V
Voltage type		AC
Breaking capacity		80 kA
Class		Class gG/gL
Application		general industrial applications
Fuse type		NSD
Fuse size		BS88/F1
Fitted with:		Offset bladed tags
Connection		Blade end
Quantity		20
Suitable for		32NNS Safeloc fuse holder SC32 Safeclip fuse holder

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		F1
Type of current		AC
Rated voltage AC	V	550
Rated voltage DC	V	
Rated current	A	2
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	0.9
Mounting holes		
Centre-to-centre distance of connections	mm	