



## Fuse-link, LV, 32 A, AC 500 V, BS88/A4, 25 x 110 mm, gL/gG, BS

## CE032

Product name		Eaton Bussmann series low voltage British standard fuse
Part no.		CE032
EAN		5027590496285
Product Length/Depth		109.5 millimetre
Product height		24.5 millimetre
Product width		21 millimetre
Product weight		77.6 gram
Compliances		RoHS Compliant CE Marked
Certifications		BS88 EAC IEC 60269
Product Tradename		None
Product Type		Low voltage British standard fuse
Product Sub Type		None
Amperage Rating		32 A
Voltage rating		500 V
Voltage type		AC
Breaking capacity		80 kA
Class		Class gG/gL
Application		general industrial applications
Fuse type		CEO
Fuse size		BS88/A4
Fitted with:		Offset bolted tags
Connection		94 mm fixing centre
Suitable for		RS100 Red spot fuse holder

## Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		A4
Type of current		AC
Rated voltage AC	V	500
Rated voltage DC	V	
Rated current	A	32
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	3.5
Mounting holes		M8
Centre-to-centre distance of connections	mm	94