

Fuse-link, LV, 30 A, AC 240 V, BS1361, 13 x 29 mm, BS



C3030

| Product name | Eaton Bussmann series low voltage British standard fuse |
|----------------------|---|
| Part no. | C3030 |
| EAN | 5027590495950 |
| Product Length/Depth | 29 millimetre |
| Product height | 12.7 millimetre |
| Product width | 12.7 millimetre |
| Product weight | 209.8 gram |
| Compliances | CE Marked RoHS Compliant |
| Certifications | IEC 60269 BS88 |
| Product Tradename | None |
| Product Type | Low voltage British standard fuse |
| Product Sub Type | None |
| | |
| Amperage Rating | 30 A |
| Voltage rating | 240 V |
| Voltage type | AC |
| Breaking capacity | 16.5 kA |
| | |
| Application | consumer unit |
| Fuse type | Consumer unit |
| Connection | Ferrule end x ferrule end |

Technical data ETIM 8.0

| Tooliilour udda ETIW 0.0 | | | | |
|---|----|---|--|--|
| Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) | | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015]) | | | | |
| Model | | Ceramic fuse | | |
| Size | | 13x29 mm | | |
| Voltage type | | AC | | |
| Rated current | Α | 30 | | |
| Rated voltage | V | 240 | | |
| Utilization category | | gL/gG (cable protection/equipment protection) | | |
| Rated operating frequency | Hz | 45 - 62 | | |
| Type of fuse status indicator | | Other | | |
| Release characteristic | | Other | | |
| Breaking capacity | kA | 16.5 | | |
| Power loss at rated current | W | 3 | | |