



Fuse-link, low voltage, 32 A, AC 240 V, BS88/E1, 12 x 47 mm, gL/gG, BS

**SSD32**

Product name		Eaton Bussmann series low voltage British standard fuse
Part no.		SSD32
EAN		5027590511803
Product Length/Depth		47 millimetre
Product height		12 millimetre
Product width		12 millimetre
Product weight		11.6 gram
Compliances		RoHS Compliant CE Marked
Certifications		IEC 60269-2 BS88
Product Tradename		None
Product Type		Low voltage British standard fuse
Product Sub Type		None
Amperage Rating		32 A
Voltage rating		240 V
Voltage type		AC
Breaking capacity		33 kA
Class		Class gG/gL
Application		street lighting cut-outs
Fuse type		SSD
Fuse size		BS88/E1
Fitted with:		Offset bladed tags
Connection		Blade end
Suitable for		SC20 Safeclip fuse holder

**Technical data ETIM 8.0**

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		E1
Type of current		AC
Rated voltage AC	V	240
Rated voltage DC	V	
Rated current	A	32
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	33
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	2.4
Mounting holes		
Centre-to-centre distance of connections	mm	