Fuse-link, LV, 200 A, AC 415 V, BS88, 31 \times 110 mm, gL/gG, BS



DE0200

Similar to illustration

Product name	Eaton Bussmann series low voltage British standard fuse
Part no.	DE0200
EAN	5027590497794
Product Length/Depth	110 millimetre
Product height	29.5 millimetre
Product width	31 millimetre
Product weight	145 gram
Compliances	RoHS Compliant
Product Tradename	None
Product Type	Low voltage British standard fuse
Product Sub Type	None
Amperage Rating	200 A
Voltage rating	415 V
Voltage type	AC
Breaking capacity	80 kA
Class	Class gG/gL
Application	general industrial applications
Fuse type	DEO
Fitted with:	Offset bolted tags
Connection	94 mm fixing centre

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)					
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])					
Fuse construction type according to IEC 60269			Other		
Type of current			AC		
Rated voltage AC		V	415		
Rated voltage DC		V			
Rated current		Α	200		
Utilization category			gL/gG (cable protection/equipment protection)		
Breaking capacity		kA	80		
Colour code			None		
Type of fuse status indicator			None		
Power loss at rated current		W	14		
Mounting holes			M8		
Centre-to-centre distance of connections		mm	93.7		