

# Transformers

- Range of 12 transformers for surface and DIN rail mounting
- Transformers to suit every bell or chime installation requirement
- All transformers operate across a voltage range of 220 to 240V ~ 50Hz
- The entire range has KEMA and VDE Certification
- The range conforms to IEC 61558-2-8
- All transformers have a “fail-safe” design. Once a short circuit occurs they cannot be reset and reused



PRODUCT	OUTPUT	SWITCH	MOUNTING TYPE	PACKAGING TYPE	PACKAGING DIMENSIONS	PACK QTY	UNIT BARCODE
D743	8V 0.5A	No	Surface	Blister	147 x 97 x 40mm	6	5004100611604
D753	8V 1A	No	Surface	Blister	147 x 97 x 40mm	6	5004100611611
D770	8V 0.5A	No	DIN/Surface	Blister	147 x 97 x 40mm	6	5004100611628
D780	8V 1A	No	DIN/Surface	Blister	147 x 97 x 40mm	6	5004100611635
D780S	8V 1A	Yes	DIN/Surface	Blister	147 x 97 x 40mm	6	5004100612137
D765	12V 1A	No	DIN/Surface	Blister	147 x 97 x 40mm	6	5004100612120
E3549	8V 1.5A	No	DIN/Surface	Blister	147 x 97 x 40mm	6	5004100612007
E3554N	8V 2A	No	DIN/Surface	Blister	147 x 97 x 40mm	6	5004100612151
E3554SN	8V 2A	Yes	DIN/Surface	Blister	147 x 97 x 40mm	6	5004100612175
E3538N	12V 1.5A	No	DIN/Surface	Blister	147 x 97 x 40mm	6	5004100612199
E3538SN	12V 1.5A	Yes	DIN/Surface	Blister	147 x 97 x 40mm	6	5004100612212
E3539N	12V 2A	No	DIN/Surface	Carton	80 x 95 x 55mm	6	5004100612236

## TRANSFORMERS WITH ISOLATION SWITCHES

- Enables isolation of the transformer’s output circuit to allow a chime or bell to be worked on in safety
- Can be used as an On/Off switch for chimes when silence is required

TRANSFORMER D780S WITH SWITCH	TRANSFORMER E3554SN WITH SWITCH	TRANSFORMER E3538SN WITH SWITCH	WHICH TRANSFORMER?	
			CHIMES	BELLS & MINI BUZZERS
			INPUT	220-240V~50 Hz
			OUTPUT	8V 1A~
			SURFACE	D753
			DIN RAIL	D780
				D780S, D770