

Fittings / LED Floodlights

Skyline Slim+ 10W LED Floodlight - 4000K



The Skyline Slim+ LED Floodlight is suitable for a wide range of applications. Available in a vast range of wattages, this low energy floodlight is ideal for any lighting project, big or small.

- Marine Grade Aluminium body.
- Fully encapsulated IP65 TUV certified driver.
- 10/20/30/50W versions are genuine replacements for Halogen Floodlights.
- 70/100/150/200W versions are genuine replacements for Metal Halide Floodlights.
- Average 8M detection range for PIR Floods.

Technical Specification

		Without PIR Symmetric							
		10W	20W	30W	50W	70W	100W	150W	200W
A	154mm	142mm	158mm	200mm	252mm	318mm	377mm	430mm	
B	83mm	84mm	138mm	170mm	225mm	276mm	305mm	355mm	
C	39mm	33mm	34mm	44mm	48mm	60mm	60mm	60mm	

		Asymmetric Without PIR			
		50W	70W	100W	200W
A	232mm	312mm	325mm	353mm	408mm
B	124mm	230mm	271mm	302mm	352mm
C	48mm	62mm	60mm	60mm	60mm

		With PIR Symmetric			
		10W	20W	30W	50W
A	170mm	180mm	200mm	230mm	300mm
B	112mm	120mm	137mm	170mm	200mm
C	68mm	68mm	72mm	72mm	72mm

Product Code

10980

Reference

Guarantee

5 Years

EAN

5013588109800

Commodity Code

9405423990

Country of Origin

CN

UNSPSC Code

39111626

Technical Specification

Volts (V)	240
Watts (W)	10
Colour Temp (K)	4000
Dimmable?	No
Lumens (lm)	1200
Life Hours	50000
Beam Angle	110°
CRI (ra)	80
Switching Cycles	25000
Frequency (Hz)	50/60
LED Drive Current	130mA
Energy Consumption (kWh/1000h)	10
IP Rating	IP65
Impact Protection	IK8

Dimensions

Height (mm)	134
Width (mm)	112
Depth (mm)	31

Packaging Information

Single Carton Height (mm)	113
Single Carton Width (mm)	63
Single Carton Depth (mm)	126
Single Carton Weight (kg)	0.42078
Individual Volume	0.0009
Outer Box Qty	12
Outer Box Height (mm)	395
Outer Box Width (mm)	232
Outer Box Depth (mm)	132
Outer Box Weight (kg)	5.40897